

STAINLESS STEEL CABLE TIES



STAINLESS STEEL CABLE TIES

Provide Unique Engineering Solutions for Demanding Applications
with High Temperatures and Corrosive Environments

- Available in Uncoated or Polyester-Coated 316 Stainless Steel
- 316 Stainless Steel - High resistance to heat, salts, & acids; perfect for indoor, outdoor, & underground applications
- Polyester Coating - Enhances the corrosive properties and acts as a barrier to avoid corrosion between dissimilar metals
- Applications - Communications, power utilities, solar, automotive, transportation, aerospace, shipping, construction, industrial, petroleum, marine, agriculture, nuclear, fire protection, signals, and signs

Uncoated Stainless Steel Cable Ties

| ACT Part Number | Length Inch/mm | Width Inch/mm | Thickness | Tie Tensile | Diameter Inch/mm | UL-CSA Mil-Spec | Per Bag | Per Case |
|-----------------|----------------|---------------|-------------|-------------|------------------|-----------------|---------|----------|
| AL-06-100-SS-C | 5.90/150.0 | .180/4.6 | .010"/.26mm | 225 lb. | 1.53/39.0 | UL | 100 | 1,000 |
| AL-08-100-SS-C | 7.87/200.0 | .180/4.6 | .010"/.26mm | 225 lb. | 1.96/50.0 | UL | 100 | 1,000 |
| AL-14-100-SS-C | 14.17/360.0 | .180/4.6 | .010"/.26mm | 225 lb. | 3.93/100.0 | UL | 100 | 1,000 |
| AL-20-100-SS-C | 20.47/520.0 | .180/4.6 | .010"/.26mm | 225 lb. | 5.90/150.0 | UL | 100 | 1,000 |
| AL-27-100-SS-C | 26.77/680.0 | .180/4.6 | .010"/.26mm | 225 lb. | 7.87/200.0 | UL | 100 | 1,000 |
| AL-08-250-SS-C | 7.87/200.0 | .310/7.9 | .010"/.26mm | 475 lb. | 1.96/50.0 | UL | 100 | 1,000 |
| AL-14-250-SS-C | 14.17/360.0 | .310/7.9 | .010"/.26mm | 475 lb. | 3.93/100.0 | UL | 100 | 1,000 |
| AL-20-250-SS-C | 20.47/520.0 | .310/7.9 | .010"/.26mm | 475 lb. | 5.90/150.0 | UL | 100 | 1,000 |
| AL-27-250-SS-C | 26.77/680.0 | .310/7.9 | .010"/.26mm | 475 lb. | 7.87/200.0 | UL | 100 | 1,000 |

Coated Stainless Steel Cable Ties

| ACT Part Number | Length Inch/mm | Width Inch/mm | Thickness | Tie Tensile | Diameter Inch/mm | UL-CSA Mil-Spec | Per Bag | Per Case |
|-------------------|----------------|---------------|-------------|-------------|------------------|-----------------|---------|----------|
| AL-08-100-SS-CT-C | 7.87/200.0 | .180/4.6 | .013"/.33mm | 200 lb. | 1.96/50.0 | UL | 100 | 1,000 |
| AL-14-100-SS-CT-C | 14.17/360.0 | .180/4.6 | .013"/.33mm | 200 lb. | 3.93/100.0 | UL | 100 | 1,000 |
| AL-20-100-SS-CT-C | 20.47/520.0 | .180/4.6 | .013"/.33mm | 200 lb. | 5.90/150.0 | UL | 100 | 1,000 |
| AL-27-100-SS-CT-C | 26.77/680.0 | .180/4.6 | .013"/.33mm | 200 lb. | 7.87/200.0 | UL | 100 | 1,000 |
| AL-08-250-SS-CT-C | 7.87/200.0 | .310/7.9 | .013"/.33mm | 300 lb. | 1.96/50.0 | UL | 100 | 1,000 |
| AL-14-250-SS-CT-C | 14.17/360.0 | .310/7.9 | .013"/.33mm | 300 lb. | 3.93/100.0 | UL | 100 | 1,000 |
| AL-20-250-SS-CT-C | 20.47/520.0 | .310/7.9 | .013"/.33mm | 300 lb. | 5.90/150.0 | UL | 100 | 1,000 |
| AL-27-250-SS-CT-C | 26.77/680.0 | .310/7.9 | .013"/.33mm | 300 lb. | 7.87/200.0 | UL | 100 | 1,000 |



Tolerance: $\pm .003"/.076mm$, 150 lb = 665 n / 300 lb = 1335 n Operating Temp. SS -76° to 572°F / SS-CT -76° to 302°F Sold in bag quantities

Related product lines



Tension Tool



Nylon 12



Cold Weather

ACT
ADVANCED CABLE TIES, INC.
245 Suffolk Lane, Gardner, MA 01440
Phone: 800.861.7228 - Fax: 978.630.3999
sales@actfs.com

